

# A-EK-1000

## Network Keyboard and Controller



### Technical Specification

#### Model

Model	A-EK-1000
-------	-----------

#### General

Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485, RS422, USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P, etc
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/ Protocol
Display	LCD, 75.2mm×33.85mm

#### Environmental

Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA
Power Consumption	5W
Working Temperature	-10C~+55C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa~106kpa
Dimension	330mm×160(140)mm×37.5(21)mm (W×D×H)(height: 100mm including joystick)
Weight	2.5kg (Including package)

### Keyboard Controls for:

- High Speed Domes
- Standalone DVRs
- Network High Speed Domes

### Functions:

- Three Dimensional Joystick Control of PTZ Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB

